

Insulated single open end wrench

110/2VDEDP



Profiles



Standards

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

Product features


- material: premium chrome vanadium steel
- head: trivalent chrome plated according to ISO 1456:2009
- made according to standard ISO 7738 and EN IEC 60900:2018




Advantages:

- double layered - double coloured insulation for additional safety
- controlled according to standard EN IEC 60900

Important!

- if second layer is visible, replace your insulated tool with a new one.



|  |  | L | B | A |  |
|--|---|-----|------|------|---|
| 618370 | 6 | 72 | 16 | 6.9 | 19 |
| 618331 | 7 | 82 | 16.1 | 6.9 | 26 |
| 617801 | 8 | 95 | 21 | 7 | 30 |
| 621575 | 9 | 100 | 24.5 | 7.5 | 35 |
| 612175 | 10 | 105 | 24.5 | 7.5 | 42 |
| 612176 | 11 | 112 | 26 | 7.5 | 51 |
| 612177 | 12 | 125 | 28 | 8 | 65 |
| 612178 | 13 | 132 | 30.5 | 8.5 | 76 |
| 612179 | 14 | 140 | 33 | 8.5 | 84 |
| 612180 | 15 | 150 | 35 | 9 | 96 |
| 621576 | 16 | 154 | 40 | 10 | 118 |
| 612181 | 17 | 157 | 40 | 10 | 137 |
| 621577 | 18 | 165 | 44 | 11 | 151 |
| 612182 | 19 | 170 | 44 | 11 | 170 |
| 618333 | 20 | 175 | 46.4 | 12.2 | 184 |
| 619201 | 21 | 180 | 48.8 | 12.5 | 213 |
| 612183 | 22 | 195 | 49 | 13 | 234 |
| 618335 | 23 | 210 | 52.8 | 13.1 | 251 |
| 612184 | 24 | 220 | 56 | 14 | 311 |
| 621578 | 26 | 235 | 59 | 15 | 361 |
| 617802 | 27 | 240 | 59 | 15 | 387 |
| 621579 | 28 | 245 | 66 | 15.8 | 440 |
| 618336 | 30 | 260 | 66.1 | 15.8 | 518 |
| 618337 | 32 | 275 | 71.4 | 17.6 | 620 |

* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

Usage (pictures)

