

# 绝缘单高颈梅花扳手

180/2VDEDP



## 配置文件



## 标准

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

## 产品属性


- 材料：铬钒钢
- 头部：根据ISO 1456:2009标准镀铬
- 根据DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018标准生产




## 优势：

- 双层 - 提供额外安全的双色绝缘
- 电测试控制

## 重要事项！

- 如果第二层可见，更换您的VDE工具



		L	B	A	
621580	6	155	13.5	8.5	51
621581	7	155	15	9	57
621582	8	160	16.5	9.5	62
621583	9	160	17.5	10	72
612185	10	162	19.5	11	81
612186	11	175	20	11.5	97
612187	12	185	21.5	11.5	112
612188	13	185	23	12.5	113
612189	14	190	25.5	13	136
612190	15	195	27	13.5	146
621584	16	190	27.5	14.5	175
612191	17	208	30.5	15.5	185
621585	18	195	30	15.5	210
612192	19	227	33	15.5	233
621586	20	245	34.5	16.2	273
619202	21	244	36.4	13.2	307
612193	22	250	37.5	17.5	300
621587	23	250	39.8	16.8	333
612194	24	255	42	18.5	428
621588	26	265	44	18	450
621589	27	270	44.8	18	411
621590	28	280	36.5	18.5	488
621591	30	310	47	19	574
621592	32	325	51.5	19.5	647

\* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.