

Ključ nasadni 1/2", izoliran

190/2VDEDP



Profili



Standardi

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

Atributi proizvoda


- materijal: krom-vanadij
- kovan, u cijelosti ojačan i zakaljen
- glava: kromirana (ISO 1456:2009)
- izrađeni prema standardu DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018




Prednosti:

- obloženi dvostrukim izolacijskim slojem sa 2 boje, koje omogućuju dodatnu sigurnost
- kontrolirano prema standardu EN IEC 60900

Važno!

- ukoliko drugi sloj postane vidljiv, alat zamijenite novim.



		D1	D2	L	T	
617803	8	18	27	54	12	65
612195	10	19,5	27	54	12	72
612196	11	20,7	27	54	12	75
612197	12	22	27	54	12	74
612198	13	23,2	27	54	12	77
612199	14	24,5	27	54	12	72
621594	15	25,7	27	54	12	78
621595	16	27	27	54	12	82
612200	17	28,1	27	54	12	83
621596	18	29,5	27	54	12	94
612201	19	30,7	27	54	14	96
621597	20	32	27	54	14	106
621598	21	33,2	27	54	14	115
612202	22	34,5	27	54	14	108
612203	24	37	27	58	16	158
617804	27	41	27	59	18	176
621602	30	44,5	27	62	22	247
621603	32	47	27	62	22	284

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Frequently asked questions

Can an insulated socket wrench be used with a normal ratchet?

A non-insulated socket wrench cannot be used with a normal ratchet because it has additional protection in the connection area.