

Alicate corte diagonal aislado

461/1VDEBI



Perfiles




Normas

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018

Características del producto

- Material: composición especial para temple y endurecimiento
- totalmente templado y revenido
- filos templados por inducción
- cabezas pulidas
- acabado: cromado según ISO 1456:2009
- mangos en doble componente para trabajos duros
- fabricada totalmente de acuerdo con ISO 5749 y EN IEC 60900



Barcode	L	B	A	C	Icon
610426	140	19	9.5	18	169
610427	160	22.5	10	22	214

capacidad de corte (10N=1Kg)

Barcode	L	max 1560 N/mm ² Ø↑	max 750 N/mm ² Ø↑
610426	140	1,6	2,0
610427	160	1,6	2,5

* Las imágenes de los productos son simbólicas. Todas las dimensiones son en mm, peso en gramos.

Preguntas frecuentes

Are certified insulated tools made through a different procedure than non-certified insulated tools?

The tools are made according to the same procedure.

Are insulated (VDE) tools considered as personal protective equipment (PPE)?

According to EU regulations, VDE tools are not considered as PPE.

Is it possible to work with insulated pliers under electrical voltage?

Yes, but only by professionals who follow safety requirements and use additional personal protective equipment.

Are the VDE tools only being sampled in series production?

The high voltage test (at 10kV) is performed fully on each tool. Other tests are performed in accordance with the EN60900 standard.