

弯曲尖嘴钳,带剪切和夹管功能

512/1VDEBI



配置文件











标准

DIN EN IEC 60900 (VDE 0682-201):2019-04; EN IEC 60900:2018


产品属性

- 材料:特种工具钢
- 落锻,完全淬火与回火
- 切削刃感应淬火
- 头部抛光
- 表面处理:依据ISO 1456:2009进行镀铬处理
- 重型双成分材料手柄
- 根据ISO 5745标准和EN IEC 60900生产

优势:

- 细长的弯曲钳口有助于简单而精准地夹紧螺母和螺钉
- 强有力的钳口展现出较强的夹紧力
- 钳口弯曲45°

● 锯齿状钳口



	L	В	D	Α	C	•
610438	170	17	2.5	9	61	152
610439	200	17	2.5	9	77	204

cutting capacity (10N=1kg)

			max 750 N/mm² Ø ī
610438	170	1,6	2,0
610439	200	1,8	2,5

^{*} Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

用途 (pictures)



Frequently asked questions

Are certified insulated tools made through a different procedure than non-certified insulated tools?

The tools are made according to the same procedure.

Are insulated (VDE) tools considered as personal protective equipment (PPE)? According to EU regulations, VDE tools are not considered as PPE.

Is it possible to work with insulated pliers under electrical voltage?

Yes, but only by professionals who follow safety requirements and use additional personal protective equipment.

Are the VDE tools only being sampled in series production?
The high voltage test (at 10kV) is performed fully on each tool. Other tests are performed in accordance with the EN60900 standard.