

Univerzalni skidač remenica

2210/2




Profili



Atributi proizvoda

- materijal: Premium Flex Plus ugljični čelik, ojačan i poboljššan
- u potpunosti poboljššan i ojačan
- površina kromirana ISO 1456:2009
- za skidanje remenica sa 3, 6 ili 9 utora
- Alat je dizajniran za demontažu pogonskih remenica sa žljebovima na čeonj strani. Alat demontira remenicu bez ikakvog rizika od oštećenja. Alat je podesiv za različite promjere remenica, jer su krakovi podešavajući.



620226

B

100

D

48 - 82

H


135




1085

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.


upotreba (pictures)




Postavite krake
izvlakača u otvore
remenice




Okretanjem ploče
podešava se položaj
kraka izvlakača, tako da
se izvlakač može čvrsto
postaviti na remenicu
koja se skida



Za pričvršćivanje
izvlakača na remenicu
okrećite vreteno u
smjeru kazaljke na satu
dok se izvlakač ne
pričvrsti




Po završetku rada,
uklonite izvlakač



Može se koristiti za...



Photo (pictures)



Rezervni dijelovi

 Vreteno za 2210/2

 Krak rezervni za 2210/2

Related products



Separator

Safety (pictures)

