


# Internal lock rings pliers, bent

538/1P



## Profiles

---



## Product features


- material: premium plus carbon steel
- drop forged, entirely hardened and tempered
- head polished
- surface finish: chrome plated to standard ISO 1456:2009
- tips black finish
- handles plastic dipped
- made according to standard DIN 5256 form D

## Advantages:

- 30% higher endurance in comparison to convenient lock rings pliers
- for diameter 8 to 100mm
- with inserted tips
- dimension 300mm with standard tips

## Usage:




- **for fitting circlips on bore holes**



|        |     |          | L   | D   | C  |     |
|--------|-----|----------|-----|-----|----|-----|
| 621211 | 140 | 8 - 13   | 128 | 0.9 | 28 | 114 |
| 621212 | 140 | 12 - 25  | 128 | 1.3 | 28 | 114 |
| 621213 | 180 | 19 - 60  | 166 | 1.8 | 38 | 194 |
| 621214 | 220 | 40 - 100 | 202 | 2.3 | 48 | 244 |
| 616743 | 300 | 85 - 140 | 295 | 3.2 | 68 | 501 |

\* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

### Usage (pictures)



Tips hardened to 58 HRC prevent bending or breaking during the removal or insertion of circlips

The tips are inserted into the jaw at an angle that prevents the circlip from sliding off the tips

### Related products

External lock rings pliers, straight

External lock rings pliers, bent

Internal lock rings pliers, straight