

Zestaw wkrętek TBI o profilu TX, we wkładce SOS

964/9CSOS



Profile




Cechy produktu

- Wkładka narzędziowa: 188 x 364 x 30 mm
- Kompatybilna z szufladami z linii Eurostyle, Eurovision, Europlus i Hercules (szuflady przednie)

Zestaw zawiera:

- 8x wkrętak z profilem TX TBI (art. 621TBI) rozm. TX 10, TX 15, TX 20, TX 25, TX 27, TX 30, TX 40, TX 45




Nazwa produktu

SKU

Artykuł

Wymiary

Ilość

Nazwa produktu	SKU	Artykuł	Wymiary	Ilość
Zestaw wkrętaków TBI o profilu TX, we wkładce SOS	621560	964/9CSOS	-	8
Wkrętak TBI o profilu TX		621TBI	TX 10, TX 15, TX 20, TX 25, TX 27, TX 30, TX 40, TX 45	8
Wkładka SOS do 964/9CSOS		vI964/9CSOS	188x364x30	1

* Przedstawiony wygląd produktu jest orientacyjny. Wszystkie wymiary są w mm, podana waga w gramach

Wskazówki bezpieczeństwa



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.