

Magnetizer-demagnetizer

633



Profili



Opis proizvoda

- materijal:ABS
- plave boje


Upotreba:

- Magentizer se koristi za vrh odvijača - namagnetišite vrh odvijača u prostoru obeleženom oznakom "+" i tada ga možete koristiti za prenošenje vijaka u prostoru koji je ograničen za manipulaciju, pre zavijanja ili nakon odvijanja vijaka.
- Vrh odvijača može se razmagnetisati u za to obeležnom prostoru, laganim prelaskom odvijača preko stepenastog profila demagnetizera.

- Trajanje namagnetisanosti zavisi od područja primene - ukoliko se odvijači koriste u prostoru sa jačim magnetnim poljima (npr. oko strujnih ormara) vrh odvijača se brže razmagnetiše. U normalnom okruženju namagnetisanost odvijača traje duže.
- Magnetizer se koristi za vrh odvijača u prostoru koji je ograničen za manipulaciju - kada vijci ne mogu direktno da se postave na mesto gde ih treba učvrstiti, ali kada se mogu pozicionirati uz pomoć namagnetisanog vrha odvijača. Slična je upotreba i pri odvijanju vijaka. Namagnetisan vrh odvijača takođe se može koristiti za podizanje sitnih metalnih objekata u ograničenom prostoru.

VAŽNO!

- Namagnetisani odvijač ne može da se koristi za prohromske vijke.



	B	A	
--	---	---	--

612866

52

30

91

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Pravilna upotreba



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.