

# Csapágylehúzó három állítható karral

682/2




Profilok



Terméjkellemzők

- anyaga: szerszámtest Premium Flex Plus szénacélból, karok Premium króm-vanádium acélból
- kovácsolt, teljes anyagában nemesített
- felületkezelés: krómozott, ISO 1456:2009 szabvány szerint, csavarorsó feketített
- a karok két pozícióban rögzíthetőek

- a lehúzó-körmök pontosan az eltávolítandó alkatrész alá illeszthetők



	N <sup>o</sup>	L $\bar{\uparrow}$	D $\bar{\uparrow}$	$\overline{F_{max}}$ $\rightarrow$	$\overline{t_{max}}$ $\rightarrow$	M	S	
612604	0	90	90	25	2.5	M 10 x 1	13	305
601767	1	130	160	40	4	M 14 x 1,5	17	1725
601768	2	190	230	50	5	M 20 x 2	22	2570
601769	3	250	300	80	8	M 22 x 2	24	5100

\* A termékeképek illusztrációk. Minden feltüntetett méret milliméterben, a tömegek grammban. Az összes feltüntetett méret eltérhet a toleranciának megfelelően.

## Használat (pictures)











## Pótalkatrészek

Lehúzókar

Csavarorsó

## Safety (pictures)



## Frequently asked questions

**Can we achieve greater pulling force using a three-arm puller compared to a two-arm puller?**

It depends on the dimensions. In principle, yes, because the force is distributed over several arms.

**One arm broke. Do I have to replace all the arms or just the broken one?**

It is necessary to change all the arms.