

Trekker, 2-armig

680/2




Profielen



Product attributen

- material: body from premium flex plus carbon steel, arm from premium chrome vanadium steel
- drop forged, entirely hardened and tempered
- surface finish: trivalent chrome plated according to ISO 1456:2009, screw blackened


- arms adjustable in two positions
- lever action claws fit closely under the part to be removed



Barcode	Nº	L↑	D↑	f _{max} →	t _{max} →	M	S	Weight
612603	0	90	90	20	2	M 10 x 1	13	405
601762	1	130	160	30	3	M 14 x 1,5	17	915
601763	2	190	230	40	4	M20 x 2	22	2078
601764	3	250	300	60	6	M 22 x 2	24	4075

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Gebruik (Afbeeldingen)



Onderdelen



Arm



Spindle

Gerelateerde producten



Trekker, 2-armig











Trekker, 2-armig



Trekker, 3-armig

Veiligheid (Afbeeldingen)



Veelgestelde vragen

Can we achieve greater pulling force using a three-arm puller compared to a two-arm puller?

It depends on the dimensions. In principle, yes, because the force is distributed over several arms.

One arm broke. Do I have to replace all the arms or just the broken one?

It is necessary to change all the arms.

