Izvlakač dvokraki klizni

683/2



Profili


Premium Flex + Premium

Atributi proizvoda

- materijal: Premium Flex Plus alatni čelik
- kovana, potpuno poboljšana i ojačana
- završna obrada: kromiranje prema standardu ISO 1456:2009, vijak bruniran
- krakove dobro pričvrstiti pod dio koji se izvlači

Prednosti:


- okretanjem krakova, izvlakač postaje unutrašnji ili vanjski



	№	L	D1	D2	Fmax	tmax	M	S	
615076	60	90	65	50 - 90	25	2.5	M 10x1	13	325
615077	90	90	90	50 - 110	25	2.5	M 10x1	13	395
615078	130	140	130	80 - 140	50	5	M 14x1,5	17	1125
615079	180	140	180	80 - 180	50	5	M 14x1,5	17	1225
615080	250	195	250	130 - 250	75	7.5	M 22x2	24	4025
615081	350	195	350	130 - 350	75	7.5	M 22x2	24	4525

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

upotreba (pictures)





Rezervni djelovi

 Krak

 Vreteno

Related products



Izvlakač dvokraki




Izvlakač dvokraki klizni



Izvlakač trokraki

Safety (pictures)



Frequently asked questions

Can we achieve greater pulling force using a three-arm puller compared to a two-arm puller?
It depends on the dimensions. In principle, yes, because the force is distributed over several arms.

One arm broke. Do I have to replace all the arms or just the broken one?
It is necessary to change all the arms.