

Momentsleutel

264



Profielen



Standaard

ISO 6789


Product attributen






- reversible ratchet head
- Torque application: one-way, but always apply in direction specified on torque wrench handle
- ratchet operates in clockwise and anti-clockwise directions
- for tightening on right hand threaded bolts and nuts
- unmistakable signal when set torque is reached
- Default value for the recalibration interval is 12 month of use, or approximately 5.000 cycles!
- made according to standard ISO 6789
- dual scaled, Nm and Kgm

Important!

- Do not use torque wrench for untightening!
- Torque tightens only in the direction showed on the key sticker! Sticker shows the proper direction of tightening!
- The default calibration interval of the torque wrench is 12 months or 5.000 measurements from the date of end user purchase.
- ALWAYS set the measuring mechanism to starting point, at the end of work.
- When the requested torque is reached, please do not tight any more.


- Torque wrench can be damaged, if manual instructions are not considered.




|  |  |  |  |  |
|--|---|---|---|---|
| 615485 | 1/4" | 2 - 24 | 270 | 686 |
| 615486 | 3/8" | 5 - 110 | 360 | 1100 |
| 615487 | 1/2" | 28 - 210 | 465 | 1680 |
| 615488 | 1/2" | 35 - 350 | 640 | 2930 |
| 615489 | 3/4" | 70 - 560 | 840 | 5600 |
| 615490 | 3/4" | 140 - 700 | 1070 | 8200 |
| 615491 | 1" | 140 - 980 | 1220 | 8800 |

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.


Gebruik (Afbeeldingen)



Unscrew the bottom bolt, to release screw for torque adjustment.




Adjust to designated torque.



Screw back bottom bolt, to fix torque adjustment.



Adjust and start tightening (prescribed torque direction). When you hear audio signal (click), the designated torque is reached. Stop tightening.



Warning! Never loosen screw marked red. In the event of unscrewing, your warranty will be void.

Foto (Afbeeldingen)



Veiligheidstips



- Only an authorised person in a certificated service centre can perform technical maintenance.
- Tools should always be serviced and calibrated by a certified service engineer.
- Tool should only be used for precise tightening as specified in the instruction manual.
- Check instruction manual on how to read the value scale on the tool properly.
- Stop tightening after hearing a feedback from the tool.
- Use only sockets with the same square drive.
- Always return the value on the scale back to 0 after usage and before storing.



Veiligheid (Afbeeldingen)

