

# Slagmoersleutel 3/8"

1541



## Profielen



## Product attributen

- free speed 10000 revolution per minutes
- max. torque 271 Nm
- maximum air pressure: 6,2 Bar
- air consumption 71 l/min
- air inlet 1/4"
- max bolt size M10

## Voordelen:


- controlled torque
- fast screwing
- wide range of use

## Gebruik:

- car industry
- aircraft industry
- agricultural equipment
- heavy industry
- larger construction machinery
- shipbuilding industry
- individual mounting

## Important!

- Always use Unior IMPACT sockets.



Barcode	Square	L	A	B	Nm	Icon
---------	--------	---	---	---	----	------

615320

3/8"

139

73,5

175

271

1350

\* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

## Foto (Afbeeldingen)



## Accessoires



Koppeling, man



Koppeling, man



Koppeling, vrouw



Koppeling, vrouw



Pneumatische filterdrukregelaar en olievernevelaar 3/8"



Pneumatische filterdrukregelaar en olievernevelaar 1/2"



Spiraalslang

## Veiligheidstips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.