Impact wrench

1561



Profiles

Product features

- free speed 8000 revolution per minutes
- max. torque 814 Nm
- maximum air pressure: 6,2 Bar
- air consumption 113 l/min
- air inlet 1/4"
- max bolt size M16

Advantages:


- controlled torque
- fast screwing
- wide range of use

Usage:

- car industry
- aircraft industry
- agricultural equipment
- heavy industry
- larger construction machinery
- shipbuilding industry
- individual mounting

Important!

- Always use Unior IMPACT sockets.



		L	A	B	Nm	
615322	1/2"	188	70	190	814	2910

* Images of products are symbolic. All dimensions are in mm, and weight is in grams. All listed dimensions may vary in tolerance.

Usage (pictures)





Photo (pictures)



Accessories

 Coupling, male part

 Coupling, male part

 Coupling, female part

 Coupling, female part

 Pneumatic filter regulator and lubricator 3/8"

 Pneumatic filter regulator and lubricator 1/2"

 Spiral pneumatic hose

Safety tips

- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.

- Always disconnect tools not in use from the air supply.

- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.