

# Odvijač pneumatski 1/2"

1561



## Profili



## Atributi proizvoda

- 8.000 o/min u slobodnom hodu
- max. okretni moment: 678 Nm
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 113 l/min
- priključak za zrak: 1/4"
- za vijke do M16

## Prednosti:


- kontroliran moment zavijanja
- brzo zavijanje
- širok spektar upotrebe

#### Upotreba:

- automobilska industrija
- avionska industrija
- poljoprivredna mehanizacija
- teška industrija
- veći građevinski strojevi
- brodogradnja
- individualna montaža

#### Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



615322	1/2"	188	70	190	814	2910

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

#### Upotreba (pictures)



#### Photo (pictures)



## Accessories



Spojnicica muška



Spojnicica muška



Spojnicica ženska



Spojnicica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Crijevo spiralno za zrak

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.



- Always disconnect tools not in use from the air supply.

- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.