

# 1/2"气锤

1561



## 配置文件



## 产品属性

- 每分钟8000转的空载转速
- 最大扭矩814 Nm
- 最大气压：6.2 Bar
- 空气消耗量113 升/分钟
- 1/4"进气口
- 最大螺栓尺寸M16

优势：


- 控制扭力
- 快速拧紧
- 应用范围广泛

### 用途:

- 汽车行业
- 航空业
- 农业设备
- 重工业
- 大型建筑机械
- 造船业
- 单独安装

### 重要事项！

- 务必使用Unior气动套筒



615322	1/2"	188	70	190	814	2910

\* Images of products are symbolic. All dimensions are in mm, and weight is in grams. All listed dimensions may vary in tolerance.

### 用途 (pictures)



### Photo (pictures)



## Accessories



气动管接头



气动管接头



气动管接头



气动管接头



3/8"气动过滤调节器和润滑器



1/2"气动过滤调节器和润滑器



螺旋气动软管

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.



- Always disconnect tools not in use from the air supply.

- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.