# 1/2"气锤

1561



## 配置文件

## 产品属性

- 每分钟8000转的空载转速
- 最大扭力814 Nm
- 最大气压：6.2 Bar
- 空气消耗量113 升/分钟
- 1/4"进气口
- 最大螺栓尺寸M16

## 优势：

- 控制扭力


- 快速拧紧
- 应用范围广泛

用途:

- 汽车行业
- 航空业
- 农业设备
- 重工业
- 大型建筑机械
- 造船业
- 单独安装

重要事项！

- 务必使用Unior气动套筒




| | | L | A | B | Nm | |
|---|---|---|---|---|---|---|
| 615322 | 1/2" | 188 | 70 | 190 | 814 | 2910 |

* Images of products are symbolic. All dimensions are in mm, and weight is in grams. All listed dimensions may vary in tolerance.

## 用途 (pictures)





Photo (pictures)



## Accessories

 气动管接头

 气动管接头

 气动管接头

 气动管接头

 3/8"气动过滤调节器和润滑器

 1/2"气动过滤调节器和润滑器

 螺旋气动软管

## Safety tips

- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.

- Always disconnect tools not in use from the air supply.

● Check the joints and ensure that the tubes and other equipment are not damaged before use.

● All tools should be gently oiled prior to being stored.

● Always store pneumatic tools in dry places away from water.

● Always use original spare parts.

● Repairs can be performed only by authorised staff people authorised by Unior d.d.