# Impact wrench

1561



## Profiles

## Product features

- free speed 8000 revolution per minutes
- max. torque 814 Nm
- maximum air pressure: 6,2 Bar
- air consumption 113 l/min
- air inlet 1/4"
- max bolt size M16

## Advantages:


- controlled torque
- fast screwing
- wide range of use

## Usage:

- car industry
- aircraft industry
- agricultural equipment
- heavy industry
- larger construction machinery
- shipbuilding industry
- individual mounting

## Important!

- Always use Unior IMPACT sockets.




| | | L | A | B | Nm | |
|---|---|---|---|---|---|---|
| 615322 | 1/2" | 188 | 70 | 190 | 814 | 2910 |

* Images of products are symbolic. All dimensions are in mm, and weight is in grams. All listed dimensions may vary in tolerance.

## Usage (pictures)






Photo (pictures)



## Accessories

 Coupling, male part

 Coupling, male part

 Coupling, female part

 Coupling, female part

 Pneumatic filter regulator and lubricator 3/8"

 Pneumatic filter regulator and lubricator 1/2"

 Spiral pneumatic hose

## Safety tips

- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.

- Always disconnect tools not in use from the air supply.

- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.