

# Odvijač pneumatski 1/2"

1562



## Profili



## Atributi proizvoda

- 7.000 o/min u slobodnom hodu
- max. okretni moment: 813 Nm
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 119 l/min
- priključak za zrak: 1/4"
- za vijke do M18

## Prednosti:

- kontroliran moment zavijanja
- brzo zavijanje
- širok spektar upotrebe

### Upotreba:

- automobilska industrija
- avionska industrija
- poljoprivredna mehanizacija
- teška industrija
- veći građevinski strojevi
- brodogradnja
- individualna montaža

### Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



615321	1/2"	204	70	192	949	2800

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

### Photo (pictures)



### Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Crijevo spiralno za zrak

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.