Odvrtač pneumatski 1/2"

1562



Profili



Opis proizvoda

- 7.000 o/min u slobodnom hodu
- max. obrtni moment: 949 Nm
- max. pritisak vazduha: 6, 2 bara
- potrošnja vazduha: 119 l/min
- priključak za vazduh: 1/4"
- za vijke do M18

Prednosti:


- kontrolisani moment zavrtanja
- brzo zavrtanje
- širok spektar upotrebe

Upotreba:

- auto-industrija
- avio-industrija
- poljoprivredna mehanizacija
- teška industrija
- veće građevinske mašine
- brodogradnja
- individualna montaža

VAŽNO!

- UVEK koristite Uniorove IMPACT nasadne ključeve i pribor



		L	A	B	Nm	
615321	1/2"	204	70	192	949	2800

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Slika (slike)



Dodatna oprema

 Spojnica muška

 Spojnica muška

 Spojnica ženska

 Spojnica ženska

 Pripremna grupa za pneumatski alat 3/8"

 Pripremna grupa za pneumatski alat 1/2"

 Crevo spiralno za vazduh

Pravilna upotreba



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.