

# Izvijač pneumatski, prihvat 3/4"

1571



## Profili



## Atributi proizvoda

- 6.500 o/min u slobodnom hodu
- Max. okretni moment: 1016 Nm
- Max. pritisak zraka: 6, 2 bara
- Potrošnja zraka: 198 l/min
- Priključak za zrak: 1/4"
- Za vijke do M24

## Prednosti:


- Kontroliran moment zatezanja
- Brzo zatezanje
- Širok spektar upotrebe








## Upotreba

- Automobilska industrija
- Avionska industrija
- Poljoprivredna mehanizacija
- Teška industrija
- Veći građevinski strojevi
- Brodogradnja
- Individualna montaža

## Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



|  |   |   |   |   |   |   |
|--|---|---|---|---|---|---|
|  |  |  |  |  |  |  |
| 615324   | 3/4"  | 236   | 80  | 240   | 1085  | 4550  |

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## Photo (pictures)



## Accessories



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Priprema grupa 3/8"



Priprema grupa 1/2"



Cijev spiralna za zrak

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.