

# Pistol pneumatic 3/4"

1571



## Profile



## Caracteristicile produsului

- viteza de rotatie 6500 rot/min
- Moment de torsiune max. 1016 Nm
- Presiunea maxima de aer comprimat: 6, 2 Bar
- Consum de aer comprimat 198 l/min
- Racord de aer 1/4"
- Diametrul maxim de strangere M 24

## Avantaje:


- moment de torsiune controlat
- insurubare rapida
- o diversitate de utilizari

## Utilizare

- industria auto
- industria aerospatuala
- echipament agricol
- industria grea
- constructia de masini
- industria de constructii navale
- montari individuale

## Important

- Folositi intotdeauna capetele chei tubulare de impact UNIOR



		<b>L</b>	<b>A</b>	<b>B</b>		
615324	3/4"	236	80	240	1085	4550

\* Imaginea produsului este simbolica. Toate dimensiunile sunt exprimate în mm, greutatea în grame.

## Photo (pictures)



## Accessories



Cuplaj, partea tata



Cuplaj, partea tata



Cuplaj, partea mama



Cuplaj, partea mama



Filtru regulator si ungator pneumatic 3/8"



Filtru regulator si ungator pneumatic 1/2"



Furtun pneumatic elicoidal

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.