

Pistol pneumatic 3/4"

1571



Profile



Caracteristicile produsului

- viteza de rotatie 6500 rot/min
- Moment de torsiune max. 1016 Nm
- Presiunea maxima de aer comprimat:6, 2 Bar
- Consum de aer comprimat 198 l/min
- Racord de aer 1/4"
- Diametrul maxim de strangere M 24

Avantaje:


- moment de torsiune controlat
- insurubare rapida
- o diversitate de utilizari

Utilizare

- industria auto
- industria aerospatiala
- echipament agricol
- industria grea
- constructia de masini
- industria de constructii navale
- montari individuale

Important

- Folositi intotdeauna capetele chei tubulare de impact UNIOR



		L	A	B		
615324	3/4"	236	80	240	1085	4550

* Imaginea produsului este simbolica. Toate dimensiunile sunt exprimate în mm, greutatea în grame.

Photo (pictures)




Accessories




Cuplaj, partea tata



Cuplaj, partea tata



Cuplaj, partea mama



Cuplaj, partea mama



Filtru regulator si ungator pneumatic 3/8"



Filtru regulator si ungator pneumatic 1/2"



Furtun pneumatic elicoidal

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.