# Pnömatik değişken uçlu çekiç 1"

1592



## Profiles




## Product features

- serbest hız dakikada 4000 devir
- maks. Tork 2439 Nm
- maksimum hava basıncı: 6,2 Bar
- hava tüketimi 340 l/dk
- hava girişi 1/2"
- maks. cıvata boyu M36

Avantajları:


- kontrollü tork
- hızlı vidalama
- geniş çeşitlilikte kullanım

Kullanım:

- araba sanayi
- uçak sanayi
- tarım ekipmanı
- ağır sanayi
- büyük inşaat makineleri
- gemi inşaat sanayisi
- bireysel montaj

Önemli!

- Her zaman Unior DARBELİ lokmalarını kullanın.




| | | L | A | B | Nm | |
|---|---|---|---|---|---|---|
| 615326 | 1" | 307 | 114 | 280 | 2439 | 12800 |

* Ürünlerin resimleri semboliktir. Bütün boyutlar mm ve ağırlık gram cinsindendir.

Photo (pictures)



## Accessories

 Bağlantı elemanı, erkek parça

 Bağlantı elemanı, dişi parça

 Pnömatik filtre düzenleme ve yağlama aleti 3/4"

 Spiral pnömatik hortum

## Safety tips

- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.

- Always disconnect tools not in use from the air supply.