

Набор отвёрток для точной механики в картонной упаковке

608CS5E



Профили



Описание товара

- 4х отвёртки крестовые PH для точной механики (арт. 615E) PH 000x60, PH 00x60, PH 0x60, PH 1x80
- 1х Отвёртка крестовая РZ для точной механики (арт. 625E) PZ 0x60

| Наименование товара | SKU | Артикул | Размеры | Количество |
|---------------------------------------------------------|--------|---------|---------------------------------------|------------|
| Набор отвёрток для точной механики в картонной упаковке | 620962 | 608CS5E | - | 5 |
| Отвёртка крестовая РН для точной механики | | 615E | PH 000x60, PH 00x60, PH 0x60, PH 1x80 | 4 |
| Отвёртка крестовая РZ для точной механики | | 625E | PZ 0x60 | 1 |

^{*} Изображения продуктов носят демонстрационный характер. Все размеры указаны в миллиметрах, вес в граммах.

Советы по безопасности



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.