

Izvijač pneumatski 1/2" sa nasadnim ključevima, u plastičnoj kutiji

1565







Profili



Atributi proizvoda

- dimenzije kutije: 346x292x83 mm

Ime proizvoda	SKU	Članak	Dimenzije	Količina
Izvijač pneumatski 1/2" sa nasadnim ključevima, u plastičnoj kutiji	615516	1565	10 - 27	17
Odvijač pneumatski 1/2"		1561	1/2"/824 Nm	1
Produžetak IMPACT 1/2"		231.4/4	1/2"x125, 1/2"x75	2
Prsten i osigurač 1/2"		231.8/4	10 - 14, 15 - 32	2
Ključ nasadni IMPACT 1/2"		231/4 6p	10, 13, 17, 19, 21, 22, 24, 27	8
Ključ nasadni IMPACT dugi 1/2"		231/4L6p	17, 19, 21, 22, 24, 27	6

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.