Klucz pneumatyczny, udarowy z nasadkami 1/2" w plastikowej skrzynce

1565



Profile

Cechy produktu

- Wymiary skrzynki : 346x292x83 mm

Nazwa produktu	SKU	Artykuł	Wymiary	Ilość
Klucz pneumatyczny, udarowy z nasadkami 1/2" w plastikowej skrzynce	615516	1565	10 - 27	19
Klucz udarowy 1/2"		1561	1/2"/824 Nm	1
Przedłużka 1/2"		231.4/4	1/2"x125, 1/2"x75	2
Akcesoria do nasadek udarowych 1/2"		231.8/4	10 - 14, 15 - 32	2
Nasadka 1/2" udarowa		231/4 6p	10, 13, 17, 19, 21, 22, 24, 27	8
Nasadka 1/2" udarowa, długa		231/4L6p	17, 19, 21, 22, 24, 27	6

* Przedstawiony wygląd produktu jest orientacyjny. Wszystkie wymiary są w mm, podana waga w gramach

Wskazówki bezpieczeństwa



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.