

专业级调圈台

1689



配置文件





产品属性

We redesigned many of its features. The base has been made stronger for improved precision and we also added conical one-size-fits-all magnetic thru-axles adapters that can be stored anywhere on the base. The arms have been made longer to accommodate 29+ wheels better and the calipers widened accordingly. Threads, springs and bearings were all revised resulting in smoother operation plus less frequent calibration. Additionally, we include white high-gloss stickers you can apply to the base and caliper arm to improve background contrast, making it easier than ever to use.

Here is a full list of the improvements.


- Stronger base for improved precision
- Longer and redesigned upright arms for improved clearance of 29+ wheels and truing precision
- Wider calipers for increased clearance of 29+ wheels
- Accommodates wider axles, works with through axle hubs up to 197mm width (include the use of adapters). Max. arm opening 230mm (without the use of adapters).
- New bearings on the upright arm adjust axle are spring loaded for improved precision and reduced frequency of calibration
- Redesigned caliper tips for easier radial truing
- Revised threads and springs for smoother operation
- 8mm bench mount holes at the bottom, 268 mm center to center
- Slicker design, all black
- Comes with conical magnetic through axle adapters one size fits all (12, 15 and 20). The adapters are
 now magnetic and can be affixed anywhere on the base. Features a bolt for more permanent fix on the
 upright arms.
- Includes white high gloss stickers, covering the base and caliper arm, for improved background contrast (stickers are not preapplied)

Compatibility:

- Accepts wheels from 16 to 29+ inch with or without tire.
- Supports solid, quick release and through axle hubs
- Through axle hubs are supported with use of the adapters (included with truing stand)
- One pair of through axle adapters support all sizes of through axles

Standard features (same as before):

- 几何形状的卡尺能够同时对轮辋进行准确的轴向控制。
- 卡尺具有塑料涂层,防止车轮标志刮掉。
- 采用直立调节旋钮可以调节垂直臂的位置,以便适合轮轴的宽度。调节卡钳臂的位置,以便适合车轮半径,调节卡钳尖端的距离,以便适合轮辋宽度。
- 当更换车轮时,弹簧加压垂直臂和卡钳臂能够快速拉开,当插入一个新车轮时,它会自动弹回设置位置。这样就能够快速修整各种相同尺寸的车轮。



	D₹	E₹	L₹	LŦ	Н	L	L1	•
629297	390	40	40	226	485	298	342	7165

^{*} Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

用途 (pictures)



















Accessories



1689调圈台校正卡尺



1689卡针



轴中心调整器





Pro Truing Stand Wooden Base

配件



卡针用的配件头



Handle for 1689