

Επαγγελματικός κεντραριστής τροχού

1689



Προφίλ



Χαρακτηριστικά προϊόντος

We redesigned many of its features. The base has been made stronger for improved precision and we also added conical one-size-fits-all magnetic thru-axles adapters that can be stored anywhere on the base. The arms have been made longer to accommodate 29+ wheels better and the calipers widened accordingly. Threads, springs and bearings were all revised resulting in smoother operation plus less frequent calibration. Additionally, we include white high-gloss stickers you can apply to the base and caliper arm to improve background contrast, making it easier than ever to use.

Here is a full list of the improvements.


- Stronger base for improved precision
- Longer and redesigned upright arms for improved clearance of 29+ wheels and truing precision
- Wider calipers for increased clearance of 29+ wheels
- Accommodates wider axles, works with through axle hubs up to 197mm width (include the use of adapters). Max. arm opening 230mm (without the use of adapters).
- New bearings on the upright arm adjust axle are spring loaded for improved precision and reduced frequency of calibration
- Redesigned caliper tips for easier radial truing
- Revised threads and springs for smoother operation
- 8mm bench mount holes at the bottom, 268 mm center to center
- Slicker design, all black
- Comes with conical magnetic through axle adapters – one size fits all (12, 15 and 20). The adapters are now magnetic and can be affixed anywhere on the base. Features a bolt for more permanent fix on the upright arms.
- Includes white high gloss stickers, covering the base and caliper arm, for improved background contrast (stickers are not preapplied)

Συμβατότητα:

- Accepts wheels from 16 to 29+ inch with or without tire.
- Supports solid, quick release and through axle hubs
- Through axle hubs are supported with use of the adapters (included with truing stand)
- One pair of through axle adapters support all sizes of through axles

Standard features (same as before):

- Η γεωμετρία των ακίδων επιτρέπει ταυτόχρονο έλεγχο του άξονα για ακριβή ρύθμιση του τροχού
- Οι ακίδες έχουν πλαστικά καλύμματα για να μην τραυματίζουν τον τροχό
- Η όρθια θέση των μπράτσων μπορεί να ρυθμιστεί ανάλογα με το πλάτος του άξονα. Η θέση των μπράτσων ρυθμίζεται σύμφωνα με τη διάμετρο του τροχού και η απόσταση των ακίδων σύμφωνα με το πάχος της ζάντας
- Όταν αφαιρείται ο τροχός, η βάση επανέρχεται αυτόματα στη θέση που έχουμε ορίσει, ώστε να δεχτεί τον επόμενο τροχό. Έτσι μπορούμε να δουλεύουμε γρήγορα σε πολλαπλούς, όμοιους τροχούς.



D↑

E↑

L↓

L↑

H

L

L1





D↑

E↑

L↓

L↑

H

L

L1



629297

390

40

40

226

485




298

342

7165

* Οι εικόνες των προϊόντων είναι συμβολικές. Όλες οι διαστάσεις είναι σε mm, το βάρος είναι σε γραμμάρια. Όλες οι αναφερόμενες διαστάσεις μπορεί να διαφέρουν σε ανοχές.

Χρήση (εικόνες)



Παρελκόμενα



Βραχίονας ακίδων για το 1689



Ακίδα για έλεγχο φρένου για το 1689



Αντάπτορας για άξονα για το 1689



Αντάπτορας κεντραριστή τροχών για Cannondale Lefty®



Ξύλινη βάση για το 1689

Ανταλλακτικά



Ανταλλακτικό δόντι για την δαγκάνα



Handle for 1689