

# Nasadka 1" uderowa, długa

233/4L6p







## Profile






## Cechy produktu

- materiał: stal chromo-wanadowa premium flex
- kuta matrycowo, całkowicie utwardzana i odpuszczana
- wykończenie powierzchni : czerniona ( fosforyzowana ) zgodnie z ISO 9717
- wykonanie zgodne ze standardem ISO 2725-2 oraz DIN 3129



		D1	D2	L	T	
616771	22	40	54	100	21	879
616772	24	42	54	100	21	921

		D1	D2	L	T	
616773	27	46	54	100	24	1012
616774	30	50	54	100	24	1075
616775	32	52	54	100	24	1090
616776	33	53	54	100	24	1109
616777	34	55	54	100	40	1162
616778	36	56	54	100	65	1207
616779	38	59	54	100	65	1222
616780	41	63	54	100	64	1367
616781	42	64	54	100	64	1380
616782	46	69	54	100	63	1613
616783	50	74	54	100	62	1793
616784	55	80	54	100	60	1976
616785	60	86	54	120	78	2726
616786	65	92	54	125	80	3192
616787	70	99	54	125	80	3595
616788	75	104	86	135	85	4512
616789	80	109	86	135	85	5532

\* Przedstawiony wygląd produktu jest orientacyjny. Wszystkie wymiary są w mm, podana waga w gramach

### Bezpieczeństwo (Obrazy)

