Izvijač plosnati NI

605NI



Profili


Premium Hard

Zatvori pretraživanje

DIN 5265, ISO 2380-1, 2

Atributi proizvoda

- oštrica od Premium Hard krom-vanadijev čelika, u cjelosti ojačana i zakaljena
- tijelo niklovano
- ručka ergonomski oblikovana
- ručica od polipropilena
- otvor u držci za vješanje
- izrađeno prema standardu ISO2380-1,2



		axb	C	L	D	
616420	SALE	0.4 x 2.5	75	160	2.5	34
616421	SALE	0.5 x 3.0	80	165	3	35

		axb	C	L	D	
616422	SALE	0.6 x 3.5	100	185	3.5	39
616423	SALE	0.8 x 4.0	100	185	4	41
616424	SALE	1.0 x 5.5	125	225	5	70
616427		1.6 x 10.0	200	320	8	173

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Safety tips

- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.

- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

Safety (pictures)

