

# Ključ nasadni 1/4" dugi

188/2L6p



## Profili




## Standardi

ISO 2725-1

## Atributi proizvoda

- materijal: krom-vanadij
- kovan, u cijelosti ojačan i zakaljen
- kromirani (ISO 1456:2009)
- izrađeni prema standardu ISO2725-1 (samo metričke dimenzije)



618697



3.2

L

50

D1

6

D2

12

T




8



20



Till end of stock

		L	D1	D2	T		
616881	4	50	6.8	11.9	5	20	Till end of stock
616882	4.5	50	7.1	11.9	5	20	Till end of stock
616883	5	50	8	11.9	5	20	Till end of stock
616884	5.5	50	8.3	11.9	5	20	Till end of stock
616885	6	50	9.3	11.9	8	20	
616886	7	50	10.5	11.9	8	31	
616887	8	50	11,9	11.9	8	71	
616888	9	50	13,1	13.1	11	71	
616889	10	50	14,5	14.5	11	71	
616890	11	50	15,8	15.8	11	71	
616891	12	50	16,8	16.8	13	71	
616892	13	50	17,8	17.8	13	71	
616893	14	50	19,6	19.6	16	71	

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## Frequently asked questions

**I attached the socket wrench to the pneumatic tool and the wall cracked. What could be wrong?**

When working with pneumatic screwdrivers, you must use an impact socket wrench.