

Socket 3/8", 12 point

238/1 12p



Profiles



Standards

ISO 2725 - 1

Product features

- material: premium flex chrome vanadium steel
- drop forged, entirely hardened and tempered
- surface finish: trivalent chrome plated according to ISO 1456:2009
- polished
- made according to standard ISO 2725-1 (only metric dimension)



|  |  | L | D1 | D2 | T↑ |  |
|--|---|----|------|------|----|---|
| 617122 | 6 | 28 | 10.2 | 16.9 | 8 | 28 |
| 616905 | 7 | 28 | 10.6 | 16.9 | 8 | 28 |
| 616906 | 8 | 28 | 11.8 | 16.9 | 8 | 29 |
| 616907 | 9 | 28 | 13.2 | 16.9 | 8 | 29 |
| 616908 | 10 | 28 | 14.5 | 16.9 | 8 | 30 |
| 616909 | 11 | 28 | 15.7 | 16.9 | 8 | 29 |
| 616910 | 12 | 28 | 16.9 | 16.9 | 8 | 28 |
| 616911 | 13 | 28 | 17.9 | 17.9 | 8 | 32 |
| 616912 | 14 | 28 | 19.6 | 17,9 | 12 | 39 |
| 616913 | 15 | 28 | 20,9 | 20,9 | 12 | 46 |
| 616914 | 16 | 30 | 21.9 | 21.9 | 12 | 48 |
| 616915 | 17 | 30 | 23.5 | 23.5 | 12 | 49 |
| 616916 | 18 | 30 | 24.7 | 21 | 12 | 65 |
| 616917 | 19 | 30 | 25.9 | 23 | 14 | 73 |
| 616918 | 20 | 32 | 27.2 | 24 | 14 | 86 |
| 616919 | 21 | 32 | 27.9 | 25 | 14 | 88 |
| 616920 | 22 | 32 | 29.7 | 26 | 14 | 105 |
| 616921 | 23 | 32 | 31.7 | 27 | 14 | 120 |
| 616922 | 24 | 32 | 31.9 | 28 | 16 | 112 |
| 616923 | 1/4" | 28 | 10.2 | 16.9 | 8 | 28 |
| 616924 | 5/16" | 28 | 11.8 | 16.9 | 8 | 29 |
| 616925 | 3/8" | 28 | 14.5 | 16.9 | 8 | 30 |
| 616926 | 7/16" | 28 | 15.7 | 16.9 | 8 | 29 |
| 616927 | 1/2" | 28 | 17,9 | 17,9 | 8 | 32 |
| 616928 | 9/16" | 28 | 19,7 | 19.7 | 12 | 39 |
| 616929 | 5/8" | 30 | 21,9 | 21.9 | 12 | 48 |

|  |  | L | D1 | D2 | T↑ |  |
|---|--|----|------|------|----|--|
| 616930 | 11/16" | 30 | 23,5 | 23.5 | 12 | 59 |
| 616931 | 3/4" | 30 | 25.9 | 23 | 14 | 73 |
| 616932 | 13/16" | 32 | 27.9 | 25 | 14 | 88 |
| 616933 | 7/8" | 32 | 29.5 | 26 | 14 | 105 |
| 616934 | 15/16" | 32 | 31.9 | 28 | 14 | 112 |
| 616935 | 1" | 32 | 33.9 | 30 | 14 | 132 |

* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

Frequently asked questions

I attached the socket wrench to the pneumatic tool and the wall cracked. What could be wrong?

When working with pneumatic screwdrivers, you must use an impact socket wrench.