

Schroevendraaierset CR

608CS5CR



Profielen



Product attributen

Set bevat

5x crosstip (PH) screwdriver CR (article 615CR) dim.PH 0x60, PH 1x80, PH 2x100, PH 3x150, PH 4x200

Productnaam	SKU	Artikel	Afmetingen	Hoeveelheid
Schroevendraaierset CR	617028	608CS5CR	-	5
Schroevendraaier, CR phillips		615CR	PH 0x60, PH 1x80, PH 2x100, PH 3x150, PH 4x200	5

^{*} Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Veiligheidstips



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

Veiligheid (Afbeeldingen)







