

Гарнитура одвртувачи CR со TX профил

621CS7CR



Profiles





Product features

Гарнитурата вклучува:

7 x одвртувач ТВI со ТХ профил (article 621CR) dim. TX 10, TX 15, TX 20, TX 25, TX 27, TX 30, TX

Product name	SKU	Article	Dimensions	Quantity
Гарнитура одвртувачи CR со ТХ профил	617031	621CS7CR	TX 10 - TX 40	7

Product name	SKU	Article	Dimensions	Quantity
Одвртка со ТХ профил CR изведба		621CR	TX 10, TX 15, TX 20, TX 25, TX 27, TX 30, TX 40	7

^{*} Сликите на производите се симболични. Сите димензии се во мм, тежината е во грамови. Сите наведени димензии може да се разликуваат во ниво на толеранција

Safety tips



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

Safety (pictures)







