

Odvijači NI u garnituri

608CS5NI





Profili



Opis proizvoda

Sadržaj:

- 4 kom. krstastih odvijača (art. 615NI), dim. PH 0x60, PH 1x80, PH 2x100, PH 3x150
- 1 kom. krstastih odvijača (art. 625NI), dim. PZ2x100

Naziv proizvoda	SKU	Artikal	Dimenzije	Količina
Odvijači NI u garnituri	617041	608CS5NI	-	5
Odvijač NI krstasti PH		615NI	PH 0x60, PH 1x80, PH 2x100, PH 3x150	4
Odvijač NI krstasti PZ		625NI	PZ 2x100	1

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Pravilna upotreba



- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.



- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.

Bezbednost (slike)

