Jeu de 6 douilles emmanchées isolées VDE 1000V TBI

629CS6VDETBI



Profils

1000V IEC 60900

Description produit

Le jeu comprend :


- 6x insulated socket wrench with VDE TBI handle (article 629VDETBI) dim. 5.5, 6, 7, 8, 10, 13

Nom du produit	SKU	Article	Dimentions	Quantité
Jeu de 6 douilles emmanchées isolées VDE 1000V TBI	617050	629CS6VDETBI	5.5 - 13	6
Douille emmanchée 6 pans isolée VDE 1000V TBI		629VDETBI	5.5, 6, 7, 8, 10, 13	6


* Les images des produits ne sont pas contractuelles. Toutes les dimensions sont en mm, les poids en


grammes.

Utilisation (pictures)




Conception de poignée ergonomique pour la protection des mains






Ergonomic handle design = protecting your hand



Large hand contact area = more torque power



Safety tips

- Use a screw holding screwdriver to get screws started in awkward, hard-to-reach areas.
- Use a stubby screwdriver in close quarters where a conventional screwdriver cannot be used.
- A rounded tip should be redressed with a file; make sure edges are straight.
- Screwdrivers used in the shop are best stored in a rack. This way, the proper selection of the right screwdriver can be quickly made.
- Keep the screwdriver handle clean; a greasy handle is apt to cause accidents.
- A screwdriver should never be used as pry bar. If it is overstressed in this manner, the blade might break and send a particle of steel into the operator's arm or even towards his eyes.
- VDE tools that have several parts, have to be assembled correctly before use.
- When working with VDE tools avoid contact with water.

- Don't use pliers on the handle of a screwdriver to get extra turning power. A wrench should only be used on the square shank or bolster of a screwdriver that is especially designed for that purpose.
- Don't expose a screwdriver blade to excessive heat as it may reduce the hardness of the blade.
- Don't use a screwdriver with a split or broken handle.
- Don't use a regular screwdriver to check a storage battery or to determine if an electrical circuit is live.
- Don't use tools that shows sign of wear and have the second layer of plastic visible.