

Pneumatische slagmoersleutel en dopsleutelset 3/4" in kunststof cassette

1575



Profielen



Product attributen

- Afmeting cassette : 393 x 331 x 95



Productnaam

SKU

Artikel

Afmetingen

Hoeveelheid

Productnaam	SKU	Artikel	Afmetingen	Hoeveelheid
Pneumatische slagmoersleutel en dopsleutelset 3/4" in kunststof cassette	617161	1575	-	7
Slagmoersleutel 3/4"		1571	3/4"/1085 Nm	1
Slagmoerdopsleutel 3/4"		232/4 6p	19, 24, 27, 32, 36, 41	6

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Veiligheidstips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.