

# Klucz pneumatyczny, udarowy z nasadkami 1/2" w metalowej skrzynce

1575





## Profile



## Cechy produktu

- Wymiary skrzynki : 393x331x95

Nazwa produktu	SKU	Artykuł	Wymiary	Ilość
Klucz pneumatyczny, udarowy z nasadkami 1/2" w metalowej skrzynce	617161	1575	-	7
Klucz udarowy 3/4"		1571	3/4"/1085 Nm	1
Nasadka 3/4" udarowa		232/4 6p	19, 24, 27, 32, 36, 41	6

\* Przedstawiony wygląd produktu jest orientacyjny. Wszystkie wymiary są w mm, podana waga w gramach

## Wskazówki bezpieczeństwa



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.