

Odvrtač pneumatski 3/4" sa nasadnim ključevima, u plastičnoj kutiji

1575



Profilii



Opis proizvoda

- dimenzije kutije: 393x331x95

Naziv proizvoda

SKU

Artikal

Dimenzije

Količina

Naziv proizvoda	SKU	Artikal	Dimenzije	Količina
Odvrtac pneumatski 3/4" sa nasadnim ključevima, u plastičnoj kutiji	617161	1575	-	7
Odvrtac pneumatski 3/4"		1571	3/4"/1085 Nm	1
Ključ nasadni IMPACT, prihvatz 3/4"		232/4 6p	19, 24, 27, 32, 36, 41	6

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzijs mogu odstupati u granicama tolerancija.

Pravilna upotreba



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.