

2 in 1 pocket spoke and cassette lockring tool

1669/4



Profielen




Product attributen

- materiaal: premium flex plus carbonstaal
- afwerking oppervlak: chemisch gezwart volgens DIN50938-norm
- The wrench is the basic working tool for cyclists extended tours.

Hoe het gereedschap te gebruiken :

- To change broken spokes on the right side of the rear wheel, the cassette has to be removed first.
- Firstly remove the rear wheel, than fit the tool onto the freewheel nut.
- Replace the rear wheel, so that the square edge of the tool presses to the frame or derailleur hanger. After that, push the pedals in the forward direction and loosen the freewheel nut. Remove the cassette and replace the broken spoke. In order to prevent the possibility that the paint on the bicycle frame is damaged, a protective plastic plate should be inserted between the key and the frame.



| 616758 | L | B | D1 | D2 | A1 | A2 | C | 20 |
|--------|----|----|------|------|-----|-----|----|----|
| 616758 | 47 | 32 | 19,5 | 23,6 | 3,4 | 1,8 | 12 | 20 |

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm, en het gewicht in grammen. Alle vermelde afmetingen kunnen variëren in tolerantie.

Gebruik (Afbeeldingen)

