

# Socket 3/8", long type, 6 point

238/1L6p



## 프로파일




## 표준

ISO 2725 - 1

## 제품 특징

- 재질: 프리미엄 플렉스 크롬 바나듐 스틸
- drop forged, entirely hardened and tempered
- surface finish: chrome plated according to ISO 1456:2009
- polished
- made according to standard ISO 2725-1 (only metric dimension)



612036



8

L

63

D1

11.8

D2




16.8

T↑

9



55

		L	D1	D2	T↑	
612037	9	63	13.2	16.8	9	58
612038	10	63	14.5	16.8	9	61
612039	11	63	15.7	16.8	12	67
612040	12	63	16.8	16	12	75
612041	13	63	17.8	16.5	12	81
612042	14	63	19.55	17	15	91
612043	15	63	20.75	18	15	117
612044	16	63	21.75	19	15	107
612045	17	63	23.3	20	15	128
612046	18	63	24.5	21	18	112
612047	19	63	25.7	23	18	147
612048	20	63	27	24	18	157
612049	21	63	27.7	25	18	165
612050	22	63	29.5	26	21	200

\* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

## 자주 묻는 질문

**공압 공구에 소켓 렌치를 부착했는데 벽에 금이 갑니다. 무엇이 잘못되었을 수 있습니까?**  
공압 드라이버로 작업할 때는 임팩트 소켓 렌치를 사용해야 합니다.