


# Odvijač pneumatski 1.1/2"

1596



## Profili



## Atributi proizvoda

- broj okretaja u slobodnom hodu: 3000/min
- max. okretni moment: 3388 Nm
- max. pritisak zraka: 6, 2 bara
- potrošnja zraka: 410 l/min
- priključak za zrak: 1/2"
- za vijke do M45

## Prednosti:

- kontroliran moment zavijanja
- brzo zavijanje
- širok spektar upotrebe

## Upotreba:

- automobilska industrija
- avionska industrija

- poljoprivredna mehanizacija
- teška industrija
- veći građevinski strojevi
- brodogradnja
- individualna montaža

### Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



		<b>B</b>	<b>L</b>		
617690	1.1/2"	550	450	3388	17800

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## Accessories



Spojnicica muška



Spojnicica ženska



Pripremna grupa 3/4"



Crijevo spiralno za zrak

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.



- Always disconnect tools not in use from the air supply.

- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.