

Izvijač pneumatski, prihvat 1.1/2"

1596



Profili



Atributi proizvoda

- Broj okretaja u slobodnom hodu: 3000/min
- Max. okretni moment: 3388 Nm
- Max. pritisak zraka: 6, 2 bara
- Potrošnja zraka: 410 l/min
- Priključak za zrak: 1/2"
- Za vijke do M45

Prednosti:

- Kontroliran moment zatezanja
- Brzo zatezanje
- Širok spektar upotrebe

Upotreba

- Automobilska industrija
- Avionska industrija

- Poljoprivredna mehanizacija
- Teška industrija
- Veći građevinski strojevi
- Brodogradnja
- Individualna montaža

Važno!

- UVIJEK koristite Uniorove IMPACT nasadne ključeve i pribor



| | | | | | |
|--------|--------|----------|----------|------|-------|
| | | B | L | | |
| 617690 | 1.1/2" | 550 | 450 | 3388 | 17800 |

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

Accessories



Spojnicica muška



Spojnicica ženska



Priprema grupa 3/4"



Cijev spiralna za zrak

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.



- Always disconnect tools not in use from the air supply.

- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.