


Odvrtlač pneumatski 1.1/2"

1596



Profili



Opis proizvoda

- broj obrtaja u slobodnom hodu: 3000/min
- max. obrtni moment: 3388 Nm
- max. pritisak vazduha: 6, 2 bara
- potrošnja vazduha: 410 l/min
- priključak za vazduh: 1/2"
- za vijke do M45

Prednosti:

- kontrolisani moment zavrtnja
- brzo zavrtnje
- širok spektar upotrebe

Upotreba:

- auto-industrija
- avio-industrija

- poljoprivredna mehanizacija
- teška industrija
- veće građevinske mašine
- brodogradnja
- individualna montaža

VAŽNO!

- UVEK koristite Uniorove IMPACT nasadne ključeve i pribor



		B	L		
617690	1.1/2"	550	450	3388	17800

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Dodatna oprema



Spojnica muška



Spojnica ženska



Pripremna grupa za pneumatski alat 3/4"



Crevo spiralno za vazduh

Pravilna upotreba



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.



- Always disconnect tools not in use from the air supply.

- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.