

Pnömatik deęişken uçlu çekiciç 1.1/2"

1596



Profiles



Product features

- 3000 devir/dakika serbest hız
- maks. tork 3388 Nm
- maksimum hava basıncı: 6,2 Bar
- hava tüketimi 410 l/dk
- hava girişı 1/2"
- maks. civata boyu M45

Avantajları:

- kontrollü tork
- hızlı vidalama
- geniş çeşitlilikte kullanım


Kullanım:

- araba sanayi
- uçak sanayi

- tarım ekipmanı
- ağır sanayi
- büyük inşaat makineleri
- gemi inşaat sanayisi
- bireysel montaj

Önemli!

- Her zaman Unior DARBELİ lokmalarını kullanın.



					
617690	1.1/2"	550	450	3388	17800

* Ürünlerin resimleri semboliktir. Bütün boyutlar mm ve ağırlık gram cinsindedir.

Accessories



Bağlantı elemanı, erkek parça



Bağlantı elemanı, dişi parça



Pnömatik filtre düzenleme ve yağlama aleti 3/4"



Spiral pnömatik hortum

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.



- Always disconnect tools not in use from the air supply.

- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.