


Slagmoersleutel

1597



Profielen



Product attributen

- free speed 3000 revolution per minutes
- max. torque 4065 Nm
- maximum air pressure: 6,2 Bar
- air consumption 435 l/min
- air inlet 1/2"
- max bolt size M52

Voordelen:

- controlled torque
- fast screwing
- wide range of use


Gebruik:

- car industry
- aircraft industry

- agricultural equipment
- heavy industry
- larger construction machinery
- shipbuilding industry
- individual mounting

Important!

- Always use Unior IMPACT sockets.



		B	L		
617691	1.1/2"	545	465	4065	18600

* Afbeeldingen van producten zijn symbolisch. Alle afmetingen zijn in mm en gewicht in gram. Alle vermelde afmetingen kunnen variëren in tolerantie.

Accessoires



Koppeling, man



Koppeling, vrouw



Pneumatische filterdrukregelaar en olieverniveelaar 3/4"



Spiraalslang

Veiligheidstips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.



- Always disconnect tools not in use from the air supply.

- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.