

气动磨砂机

1510



配置文件



产品属性

- 每分钟10000转的空载转速
- 最大气压：6.2 Bar
- 空气消耗量212 升/分钟
- 1/4"进气口
- 尼龙磨砂垫


优势：



- 把手的人体工程形状可实现良好的握持并防止滑动。
- 适合惯用右手或左手人士
- 安静有力的驱动
- 易用开关
- 将废弃物放入袋中，使工作场所保持整洁
- 灵活耐用的软管用于清洁灰尘

- 不可远离操作平台边缘
- 将震动减至最少以优化工作条件
- 此重量产生的极限功率(1.2 kg)

用途:

- 汽车车间
- 不同工作台的准备工作，以进行后续工艺
- 适合研磨结构钢、金属和木材
- 磨砂机VELCRO™可快速、简单安全的安装和拆卸各种磨砂片.此系统适用于各种情况 - 已知最好的例子是带有VELCRO™紧固的训练鞋。



	Nº	L	A	D	
617733	2.5	220	105	150	1600
617713	5	220	105	150	1615

* Images of products are symbolic. All dimensions are in mm, and weight in grams. All listed dimensions may vary in tolerance.

用途 (pictures)




Photo (pictures)



Accessories



气动管接头



气动管接头



气动管接头



气动管接头



3/8"气动过滤调节器和润滑器



1/2"气动过滤调节器和润滑器



螺旋气动软管

Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.