

# Čekić pneumatski

1514



## Profili



## Atributi proizvoda


- pogodan za sječenje lima, vijaka, skidanje varova, betona i keramike
- u kompletu sa oprugom i brzosteznom glavom
- dužina glave: kod dim. 170 - 67 mm, kod dim. 225 - 92 mm
- dužina udarca: 9,1 mm
- broj udaraca: kod dim. 170 - 3000/min, kod dim. 225 - 2100/min
- potrošnja zraka: 250 l/min
- priključak za zrak: 1/4"



## Prednosti:

- lak i kompaktan alat, pogodan za ograničen prostor
- širok spektar upotrebe
- promjenjiva glava

## Upotreba:

- automobilska industrija
- rezanje limova i vijaka
- za odstranjivanje varova
- za rad na zidovima, betonu, kamenu, cigli, čeliku, lakim metalima



	L	B	D	
617714	170	150	19	1810
617715	225	150	19	2160

\* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

## Upotreba (pictures)



## Photo (pictures)



## Accessories



Opruga za art. 1514



Glava brzostezna za art. 1514



Sjekač plosnati



Špica



Sjekač za varove



Sjekač za lim sa rascjepom



Spojnicica muška



Spojnicica muška



Spojnicica ženska



Spojnicica ženska



Pripremna grupa 3/8"



Pripremna grupa 1/2"



Crijevo spiralno za zrak

## Safety tips



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.



- Always disconnect tools not in use from the air supply.

- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.